PRODUCT CATALOGUE

Remi Micro Centrifuge Model RM-03 Plus



Listed product | Product and model identity follow the named manufacturer.

A microcentrifuge with a 12-place closed rotor, BLDC motor and imbalance cut-off.

View product details on jayantiscientific.com

Key features

- Backlit LCD; speed and time settings.
- Manufacturer standard pack includes a microtube rotor, reductions and a PCR-strip rotor.

Technical specifications

Specification	Details
Maximum speed / RCF	15,000 rpm / 15,596 x g
Rotor capacity	12-place closed rotor with metal safety lid
Display	Large backlit LCD
Imbalance detection	Auto cut-off
Noise level	Less than 60 dB

Technical specifications (continued)

Specification	Details
Motor	Brushless DC (BLDC)
Timer setting	1-999 minutes
Speed / time setting	500-15,000 rpm; minute/second timer
Dimensions	230 x 262 x 131 mm
Standard-pack rotors/adaptors	12-place 1.5/2.0 mL microtube rotor; reductions for 0.2 mL and 0.4/0.5 mL tubes; PCR-strip rotor 2 x 8 x 0.2 mL with metal safety lid

Supplied configuration

RM-03 Plus micro centrifuge with the manufacturer rotor / adaptor configuration stated in the specification table.

NEED A QUOTATION?

Request a current quotation. Share quantity, delivery PIN code and accessory requirements.
WhatsApp 9811167934 | Call 9811167934 | 8368700634
jayantiscientific97@gmail.com | Jayanti contact page

This product catalogue is prepared by Jayanti Scientific Instruments. Manufacturer and model names identify the listed product. Technical data follows the identified manufacturer model. Optional accessories are identified separately; performance depends on the stated operating conditions.

7-UA Pista Niwas Building, Jawahar Nagar, Delhi 110007 | GSTIN 07AAOPG2165J1ZK