PRODUCT CATALOGUE

LABTRONICS Deluxe Conductivity Meter Model: LT-26



Listed product | Product and model identity follow the named manufacturer.

Labtronics LT-26 Deluxe conductivity meter; the company brochure groups LT-16 and LT-26 in one shared specification sheet and distinguishes their temperature-compensation modes.

View product details on jayantiscientific.com

Key features

- Automatic selection across five conductivity ranges.
- Digital cell-constant adjustment; platinum DIP-type measuring cell.

Technical specifications

Specification	Details
Display	312-digit LED
Measurement	Conductivity
Range selection	Automatic
Temperature measurement range	-5 to 110 deg C
Conductivity accuracy	+/-0.5% FS +/-1 digit
Temperature accuracy	+/-0.1 deg C +/-1 digit
Temperature compensation	Automatic, 0 to 50 deg C (LT-26 only)

Technical specifications (continued)

Specification	Details
Cell constant	Digitally adjustable
Measuring cell	Platinum DIP type
Cell-constant measurement	Automatic
Power	230 V +/-10% AC
Dimensions (L x B x H)	270 x 202 x 80 mm
Weight	Approx. 0.8 kg
Conductivity ranges	5 automatic ranges

Supplied configuration

Company brochure lists a conductivity cell, operation manual, dust cover, cell stand, and a temperature probe with LT-26.

NEED A QUOTATION?

Request a current quotation. Share quantity, delivery PIN code and accessory requirements.
WhatsApp 9811167934 | Call 9811167934 | 8368700634
jayantiscientific97@gmail.com | Jayanti contact page

This product catalogue is prepared by Jayanti Scientific Instruments. Manufacturer and model names identify the listed product. Technical data follows the identified manufacturer model. Optional accessories are identified separately; performance depends on the stated operating conditions.

7-UA Pista Niwas Building, Jawahar Nagar, Delhi 110007 | GSTIN 07AAOPG2165J1ZK